

# Product data sheet

Specifications



## TeSys Deca Manual Starter and Protector, auxiliary contact block, 1 NO and 1 NC, side mount, screw clamp

GVAN11

Product availability: Stock - Normally stocked in distribution facility

Price\*: 35.70 USD

### Main

|                           |   |
|---------------------------|---|
| Range                     | TeSys<br>TeSys Deca                                     |
| Device Short Name         | GVAN  |
| Product Or Component Type | Auxiliary contact block                                 |
| Product Compatibility     | GV2ME<br>GV2RT<br>GV2L<br>GV3P<br>GV3L<br>GV2LE<br>GV2P |
| Mounting Location         | Left side   |
| Pole Contact Composition  | 1 NO + 1 NC   |

### Complementary

|   |   |
|---|---|
| [Ui] Rated Insulation Voltage               | 600 V UL 508<br>690 V IEC 60947-1<br>600 V CSA C22.2 No 14  |
| [Ue] Rated Operational Voltage              | 48...690 V AC<br>24...240 V DC  |
| [Ith] Conventional Free Air Thermal Current | 6 A   |
| Mechanical Durability                       | 100000 cycles   |
| Minimum Switching Current                   | 5 mA  |
| Minimum Switching Voltage                   | 17 V  |
| Protection Type                             | GB2CB... circuit breaker<br>GG fuse 10 A  |
| Rated Operational Power In Va               | 300 VA 48 V AC-15 100000 cycles<br>414 VA 690 V AC-15 100000 cycles<br>500 VA 110...127 V AC-15 100000 cycles<br>500 VA 500 V AC-15 100000 cycles<br>650 VA 440 V AC-15 100000 cycles<br>720 VA 230...240 V AC-15 100000 cycles<br>850 VA 380...415 V AC-15 100000 cycles |
| Rated Operational Power In W                | 120 W 240 V DC-13 100000 cycles<br>140 W 110 V DC-13 100000 cycles<br>140 W 24 V DC-13 100000 cycles<br>180 W 60 V DC-13 100000 cycles<br>240 W 48 V DC-13 100000 cycles  |
| Tightening Torque                           | 12.39 lbf.in (1.4 N.m) screw clamp terminals  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|            |                       |
|------------|-----------------------|
| Height     | 3.50 in (89 mm)       |
| Width      | 0.37 in (9.3 mm)      |
| Depth      | 2.60 in (66 mm)       |
| Net Weight | 0.11 lb(US) (0.05 kg) |
| Color      | Dark grey             |

## Environment

|                              |                    |
|------------------------------|--------------------|
| Environmental Characteristic | Normal environment |
| Product Certifications       | UKCA               |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10I1122367  |
| Discount Schedule | 0I11          |
| Gtin              | 3389110343489 |
| Returnability     | Yes           |
| Country Of Origin | US            |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type Of Package 1       | PCE                    |
| Number Of Units In Package 1 | 1                      |
| Package 1 Height             | 0.59 in (1.500 cm)     |
| Package 1 Width              | 2.76 in (7.000 cm)     |
| Package 1 Length             | 3.54 in (9.000 cm)     |
| Package 1 Weight             | 1.62 oz (46.000 g)     |
| Unit Type Of Package 2       | BB1                    |
| Number Of Units In Package 2 | 10                     |
| Package 2 Height             | 3.74 in (9.500 cm)     |
| Package 2 Width              | 3.94 in (10.000 cm)    |
| Package 2 Length             | 5.98 in (15.200 cm)    |
| Package 2 Weight             | 17.99 oz (510.000 g)   |
| Unit Type Of Package 3       | S02                    |
| Number Of Units In Package 3 | 60                     |
| Package 3 Height             | 5.91 in (15.000 cm)    |
| Package 3 Width              | 11.81 in (30.000 cm)   |
| Package 3 Length             | 15.75 in (40.000 cm)   |
| Package 3 Weight             | 7.26 lb(US) (3.294 kg) |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

**Circularity Profile**

[End of Life Information](#)

**California Proposition 65**

WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Connections and Schema

---

GVAN11

